

West Central Incorporated, 2700 Trott Ave. SW, PO Box 897, Willmar, MN 56201

IN CASE OF EMERGENCY CALL CHEMTREC

UNITED STATES: 1-800-424-9300

INTERNATIONAL: 1-202-483-7616

## MATERIAL SAFETY DATA

### 1. PRODUCT IDENTIFICATION

PRODUCT NAME:	<b>Sedate</b>
SYNONYMS:	Water dispersible vegetable oil blend
CHEMICAL FAMILY:	Proprietary Blend
GENERIC DESCRIPTION:	NA
MOLECULAR WEIGHT:	NA

### 2. HAZARDOUS INGREDIENTS

#### OSHA REGULATED COMPONENTS

COMPONENT	CAS. NO.	WT %	EXPOSURE LIMITS
Phosphoric Acid	7664-38-2	<1	1mg/m <sup>3</sup>

The maximum of 1 ppm Ethylene Oxide (EO) (75-21-8) may be present in the product. The OSHA PEL and ACGIH TLV for EO is 1 ppm.

### 3. EFFECTS OF OVEREXPOSURE

EYE:	May cause eye burns.
SKIN:	May cause skin burns.
INHALATION:	Mists or vapors are harmful to respiratory tract.
ORAL:	Harmful if swallowed.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data, and/or expert review of the product. Overexposure to any chemical may result in enhancement of pre-existing adverse medical condition and allergic reactions.

### 4. EMERGENCY FIRST AID

#### CALL A POISON CONTROL CENTER OR DOCTOR IMMEDIATELY FOR TREATMENT ADVICE.

IF SWALLOWED:	Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF ON SKIN OR CLOTHING:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.
IF INHALED:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth if possible.
IF IN EYES:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses if present, after the first 5 minutes, then continue rinsing eye. Have the product container with you when calling a poison control center or doctor, or going for treatment.

---

## 5. REACTIVITY DATA

STABILITY:	Stable
CONDITIONS TO AVOID:	Excessive heat and open flames.
POLYMERIZATION:	Will not occur.
INCOMPATIBILITY:	Strong oxidizing agents. Can react with metals, strong bases and amines.
DECOMPOSITION:	Carbon dioxide, carbon monoxide, and phosphorous oxides.

---

## 6. PHYSICAL PROPERTIES

APPEARANCE AND ODOR:	Amber liquid, oily
BOILING POINT:	NA
MELTING POINT:	NA
VAPOR PRESSURE (mmg of Hg):	NA
SPECIFIC GRAVITY:	.985(+/- .05)
VAPOR DENSITY (AIR=1):	NA
EVAPORATION RATE (Butyl A.)r=1):	NA
SOLUBILITY IN WATER:	Soluble
pH (0.25%)	4 - 6

---

## 7. NFPA HAZARD RATING (National Fire Protection Association)

Flammability	HEALTH:	Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
1		
Health 2	0 Instability	FLAMMABILITY: Must be preheated before ignition can occur.
—		INSTABILITY: Normally stable, even under fire exposure conditions, and are not reactive with water.
Special Hazard		

---

## 8. FIRE AND EXPLOSION HAZARD INFORMATION

FLASHPOINT:	>200°F (Pensky-Martens closed cup ASTM D93)
FLAMMABLE LIMITS:	Not Available
EXTINGUISHING MEDIA:	Foam, Dry Chemical, CO <sub>2</sub> , Water Spray
FIRE FIGHTING:	Use alcohol-type or universal-type foams on larger fires. Smaller fires should be extinguished with carbon dioxide or dry chemical. Do not use water or foam directly on the fire. Use self-contained breathing apparatus with fighting any fire in an enclosed area.
UNUSUAL FIRE HAZARD:	May be ignited by heat, sparks, or flames. Vapors may travel to a source of ignition and flash back. Containers may explode in heat of fire.

---

## 9. SPECIAL PRECAUTIONS

HANDLING AND STORAGE:	Keep out of reach of children. Store in cool dry place. Keep in original container tightly closed. Do not reuse empty container.
OTHER PRECAUTIONS:	Do not store with food, feed, or other material to be used or consumed by humans or animals. Do not contaminate water supplies. Do not store with materials labeled "Oxidizers" or oxidizing agents.

---

## 10. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH/OSHA approved respirator if necessary.  
VENTILATION: Normal room ventilation (mechanical) should be satisfactory.  
PROTECTIVE GLOVES: Impervious.  
EYE PROTECTION: Wear goggles or a face shield.  
OTHER PROTECTION: Full body protective suit, eye wash, and safety shower. Wash with soap and water before eating, drinking, smoking or using toilet facilities.

---

## 11. SPILL OR LEAK PROCEDURES

SPILLS OR RELEASES: Material should be collected and disposed in proper manner. Avoid Discharge to natural waters as concentrated material is highly toxic to fish.  
WASTE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Dispose of in an approved waste disposal facility in accordance with all Federal, State and Local Regulations.  
CONTAINER DISPOSAL: Triple rinse (or equivalent) adding rinse water to application tank. Offer container for recycling or dispose of in a sanitary landfill or by other procedures approved by local regulations.  
Wear suitable protective equipment.

---

## 12. REGULATORY INFORMATION

COMPOUNDS WHICH REQUIRE REPORTING UNDER SARA TITLE III

Sara regulated compounds	% Wt.	Acute	Chronic	Fire	Reactivity	Pressure	CAS NO.
Phosphoric Acid	<1	yes	no	yes	no	no	7664-38-2

---

## 13. OTHER INFORMATION

WARNING! This product contains a detectable amount of ethylene oxide, which is known to the State of California to cause cancer and/or reproductive toxicity.

Ethoxylated products may contain residual amounts of ethylene oxide (EO) which can accumulate in the container headspace and be released into the ambient environment. This process is enhanced when the product is agitated, as during tank car loading and unloading, and blending operations. Ethylene oxide causes tumors in laboratory animals. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1 ppm for an eight-hour time weighted average exposure. The standard regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with OSHA ethylene oxide standard (29) CFR 1910.1047).

---

The recommendation for safe handling and protection procedures are believed to be generally suitable for the standard uses of this compound. However, each user should identify his intended uses of this material and determine whether they are appropriate. All data included in this document is released as typical values and should not be utilized to determine the suitability of this material for a particular use or purpose. No warranty, either expressed or implied, is hereby made, nor do we give permission, inducement, or recommendations to practice any patented invention without a license. All data is offered for consideration, investigation, and verification purposes only.

**West Central Incorporated**  
2700 Trott Ave. SW  
PO Box 897  
Willmar, MN 56201