

Material Safety Data Sheet

Dow AgroSciences LLC

Product Name: N-SERVE* 24 Nitrogen Stabilizer

Issue Date: 11/17/2008
Print Date: 06 Mar 2009

Dow AgroSciences LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Product and Company Identification

Product Name

N-SERVE* 24 Nitrogen Stabilizer

COMPANY IDENTIFICATION

Dow AgroSciences LLC A Subsidiary of The Dow Chemical Company 9330 Zionsville Road Indianapolis, IN 46268-1189 USA

Customer Information Number: 800-992-5994

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 800-992-5994 **Local Emergency Contact**: 800-992-5994

2. Hazards Identification

Emergency Overview
Color: Colorless to yellow
Physical State: Liquid
Odor: Aromatic
Hazards of product:

CAUTION! May cause skin irritation. May cause eye irritation. May cause central nervous system effects; may cause respiratory tract irritation.

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Health Effects

Eye Contact: May cause moderate eye irritation. Corneal injury is unlikely.

Skin Contact: Brief contact may cause skin irritation with local redness. Effects may be slow to heal.

May cause drying and flaking of the skin.

^{*} Indicates a Trademark

^{*} Indicates a Trademark of Dow AgroSciences LLC

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Skin Sensitization: Has demonstrated the potential for contact allergy in mice.

Inhalation: Prolonged excessive exposure to mist may cause adverse effects. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

Issue Date: 11/17/2008

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Effects of Repeated Exposure: For the active ingredient(s): In animals, effects have been reported on the following organs: Kidney. Liver. Blood. Female reproductive organs. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use. For the solvent(s): In animals, effects have been reported on the following organs: Kidney. Liver. Blood. For the major component(s): In animals, effects have been reported on the following organs: Liver. Respiratory tract. Blood. Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans. For the minor component(s): Cataracts were observed in rats exposed to cumene vapors.

Cancer Information: For the active ingredient(s): Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans. For the minor component(s) Cumene. Has caused cancer in laboratory animals. However, the relevance of this to humans is unknown.

Birth Defects/Developmental Effects: For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. For the solvent(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Has caused birth defects in lab animals only at doses producing severe toxicity in the mother. For the major component(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects.

Reproductive Effects: For the minor component(s) In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

3. Composition Information

Component	CAS#	Amount
Nitrapyrin	1929-82-4	22.2 %
1,2,4-Trimethylbenzene	95-63-6	18.9 %
Xylene	1330-20-7	11.4 %
1,3,5-Trimethylbenzene	108-67-8	5.0 %
Cumene	98-82-8	2.5 %
Balance		40.0 %

4. First-aid measures

Eye Contact: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice.

Skin Contact: Take off contaminated clothing. Wash skin with soap and plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of properly. **Inhalation:** Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice.

Ingestion: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Notes to Physician: If breathing is difficult, oxygen should be administered by qualified personnel. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the

Product Name: N-SERVE* 24 Nitrogen Stabilizer

clinical condition of the patient. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or doctor, or going for treatment.

Issue Date: 11/17/2008

Medical Conditions Aggravated by Exposure: Skin contact may aggravate preexisting dermatitis.

5. Fire Fighting Measures

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. General purpose synthetic foams (including AFFF type) or protein foams are preferred if available. Alcohol resistant foams (ATC type) may function.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Consider feasibility of a controlled burn to minimize environment damage. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Dense smoke is produced when product burns.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Hydrogen chloride. Carbon monoxide. Carbon dioxide.

6. Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Contain spilled material if possible. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact Dow AgroSciences for clean-up assistance. Pump with explosion-proof equipment. If available, use foam to smother or suppress.

Personal Precautions: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: Keep out of reach of children. Do not swallow. Avoid breathing vapor or mist. Avoid contact with eyes, skin, and clothing. Use with adequate ventilation. Wash thoroughly after handling.

Issue Date: 11/17/2008

Other Precautions: No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Electrically ground and bond all equipment. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Storage

Store in original container. Keep container tightly closed. Do not store near food, foodstuffs, drugs or potable water supplies. Minimize sources of ignition, such as static build-up, heat, spark or flame.

8. Exposure Controls / Personal Protection

Exposure Limits			
Component	List	Туре	Value
Nitrapyrin	ACGIH ACGIH OSHA Table Z-1	TWA STEL PEL Respirable	10 mg/m3 20 mg/m3 5 mg/m3
	OSHA Table Z-1	fraction. PEL Total dust.	15 mg/m3
Xylene	ACGIH ACGIH OSHA Table Z-1	TWA STEL PEL	100 ppm BEI 150 ppm BEI 435 mg/m3 100 ppm
1,3,5-Trimethylbenzene	ACGIH	TWA	25 ppm
Cumene	ACGIH OSHA Table Z-1	TWA PEL	50 ppm 245 mg/m3 50 ppm SKIN
1,2,4-Trimethylbenzene	ACGIH	TWA	25 ppm

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING. A BEI notation following the exposure guideline refers to a guidance value for assessing biological monitoring results as an indicator of the uptake of a substance from all routes of exposures. A "skin" notation following the inhalation exposure guideline refers to the potential for dermal absorption of the material including mucous membranes and the eyes either by contact with vapors or by direct skin contact.

It is intended to alert the reader that inhalation may not be the only route of exposure and that measures to minimize dermal exposures should be considered.

Personal Protection

Eye/Face Protection: Use chemical goggles.

Skin Protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before reuse or dispose of properly. Items which cannot be decontaminated, such as shoes, belts and watchbands, should be removed and disposed of properly.

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Issue Date: 11/17/2008

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In misty atmospheres, use an approved particulate respirator. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. The following should be effective types of airpurifying respirators: Organic vapor cartridge with a particulate pre-filter.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

9. **Physical and Chemical Properties**

Physical State Liquid

Color Colorless to yellow

Odor Aromatic

Flash Point - Closed Cup 40 °C (104 °F) Tag Closed Cup ASTM D56

Flammable Limits In Air Lower: 1.0 %(V) Literature **Upper**: 7.0 %(V) *Literature*

No test data available **Autoignition Temperature**

4 mmHg @ 20 °C Literature Approx. **Vapor Pressure Boiling Point (760 mmHg)** 161 °C (322 °F) Literature Approx..

Vapor Density (air = 1) 3.7 Literature Calculated

Specific Gravity (H2O = 1) 0.98 Literature

Liquid Density 0.98 g/cm3 Literature **Freezing Point** No test data available **Melting Point** No test data available Literature Immiscible

Solubility in Water (by

weight)

рΗ No test data available Decomposition No test data available

Temperature

10. Stability and Reactivity

Stability/Instability

Thermally stable at recommended temperatures and pressures.

Conditions to Avoid: Active ingredient decomposes at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems. Avoid static discharge.

Incompatible Materials: Avoid contact with: Acids. Oxidizers. Avoid contact with metals such as: Aluminum alloys. Magnesium. Magnesium alloys.

Product Name: N-SERVE* 24 Nitrogen Stabilizer Issue Date: 11/17/2008

Hazardous Polymerization

Will not occur.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen chloride. Nitrogen oxides. Toxic gases are released during decomposition.

11. Toxicological Information

Acute Toxicity

Ingestion

LD50, Rat, female 1,405 mg/kg

Skin Absorption

LD50, Rat, male and female > 5,000 mg/kg

Inhalation

LC50, 4 h, Aerosol, Rat, male and female > 6.0 mg/l

Sensitization

Skin

Has demonstrated the potential for contact allergy in mice.

Repeated Dose Toxicity

For the active ingredient(s): In animals, effects have been reported on the following organs: Kidney. Liver. Blood. Female reproductive organs. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use. For the solvent(s): In animals, effects have been reported on the following organs: Kidney. Liver. Blood. For the major component(s): In animals, effects have been reported on the following organs: Liver. Respiratory tract. Blood. Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans. For the minor component(s): Cataracts were observed in rats exposed to cumene vapors.

Chronic Toxicity and Carcinogenicity

For the active ingredient(s): Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans. For the minor component(s) Cumene. Has caused cancer in laboratory animals. However, the relevance of this to humans is unknown. For the major component(s): Xylene was not found to be carcinogenic in a National Toxicology Program bioassay in rats and mice.

Developmental Toxicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. For the active ingredient(s): Did not cause birth defects in laboratory animals. For the solvent(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Has caused birth defects in lab animals only at doses producing severe toxicity in the mother. For the major component(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects.

Reproductive Toxicity

For the active ingredient(s): For the major component(s): In animal studies, did not interfere with reproduction. For the minor component(s) In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

Genetic Toxicology

For the active ingredient(s): For the component(s) tested: In vitro genetic toxicity studies were negative. For the active ingredient(s): For the component(s) tested: Animal genetic toxicity studies were negative.

12. Ecological Information

Product Name: N-SERVE* 24 Nitrogen Stabilizer Issue Date: 11/17/2008

ENVIRONMENTAL FATE

Data for Component: Nitrapyrin

Movement & Partitioning

Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). Potential for mobility in soil is medium (Koc between 150 and 500).

Partition coefficient, n-octanol/water (log Pow): 3.41 Measured Partition coefficient, soil organic carbon/water (Koc): 420 Measured

Bioconcentration Factor (BCF): 33 - 230; fish; Measured

Persistence and Degradability

Chemical degradation (hydrolysis) is expected in the environment within days to weeks.

Degradation is expected in the soil environment within days to weeks.

Theoretical Oxygen Demand: 0.97 mg/mg

Data for Component: 1,2,4-Trimethylbenzene

Movement & Partitioning

Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3

and 5). Potential for mobility in soil is low (Koc between 500 and 2000).

Henry's Law Constant (H): 6.16E-03 atm*m3/mole; 25 °C Measured

Partition coefficient, n-octanol/water (log Pow): 3.63 Measured Partition coefficient, soil organic carbon/water (Koc): 720 Estimated

Bioconcentration Factor (BCF): 33 - 275; common carp (Cyprinus carpio); Measured

Persistence and Degradability

Material is expected to biodegrade only very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
1.670E-11 cm3/s	0.641 d	Estimated

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
4 - 18 %	28 d	OECD 301C Test

Theoretical Oxygen Demand: 3.19 mg/mg

Data for Component: Xylene

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is medium (Koc between 150 and 500).

Henry's Law Constant (H): 7.45E-03 atm*m3/mole; 25 °C Estimated Partition coefficient, n-octanol/water (log Pow): 3.12 Measured Partition coefficient, soil organic carbon/water (Koc): 443 Estimated

Bioconcentration Factor (BCF): 15 - 21; fish; Measured

Persistence and Degradability

Material is expected to be readily biodegradable.

Indirect Photodegradation with OH Radicals

Rate Constant	Atmosphe	eric Half-life	Method
6.5E-12 cm3/s	19).7 h	Estimated
Biological oxygen den	nand (BOD):		
BOD 5	BOD 10	BOD 20	BOD 28
37 %	58 %	72 %	

Theoretical Oxygen Demand: 3.17 mg/mg

Data for Component: 1,3,5-Trimethylbenzene

Movement & Partitioning

Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). Potential for mobility in soil is low (Koc between 500 and 2000).

Henry's Law Constant (H): 1.97E-02 atm*m3/mole; 25 °C Estimated

Partition coefficient, n-octanol/water (log Pow): 3.42 Measured

Partition coefficient, soil organic carbon/water (Koc): 700 Estimated

Bioconcentration Factor (BCF): 23 - 342; fish; Measured

Distribution in Environment: Mackay Level 1 Fugacity Model:

Air	Water.	Biota	Soil	Sediment
97.26 %	0.62 %	< 0.01 %	2.08 %	0.05 %

Issue Date: 11/17/2008

Persistence and Degradability

Material is not readily biodegradable according to OECD/EC guidelines.

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
3.51E-11 cm3/s	3.7 h	Estimated

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method
0 %	28 d	OECD 301C Test

Theoretical Oxygen Demand: 3.19 mg/mg

Data for Component: Cumene

Movement & Partitioning

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is low (Koc between 500 and 2000).

Henry's Law Constant (H): 1.15E-02 atm*m3/mole; 25 °C Measured Partition coefficient, n-octanol/water (log Pow): 3.4 - 3.7 Measured

Partition coefficient, soil organic carbon/water (Koc): 800 - 2,800 Estimated

Bioconcentration Factor (BCF): 35.5; fish; Measured

Distribution in Environment: Mackay Level 1 Fugacity Model:

Air	Water.	Biota	Soil	Sediment
98.38 %	0.33 %	< 0.01 %	1.26 %	0.03 %

Persistence and Degradability

Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
6.90E-12 cm3/s	1.55 d	Estimated
OECD Biodegradation Tests:		
Biodegradation	Exposure Time	Method
86 %	28 d	OECD 301D Test

	0			, u	•	3E 0B 001B 1000
Ī	Biological oxygen der					
	BOD 5	ВО	D 10	BOD 20		BOD 28
	40 %	62	2 %	70 %		

Theoretical Oxygen Demand: 3.20 mg/mg

ECOTOXICITY

Data for Component: Nitrapyrin

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in most sensitive species tested). Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg). Material is slightly toxic to birds on a dietary basis (LC50 between 1001 and 5000 ppm).

Fish Acute & Prolonged Toxicity

LC50, bluegill (Lepomis macrochirus), static, 96 h: 3.4 - 7.9 mg/l

LC50, rainbow trout (Oncorhynchus mykiss), static, 96 h: 4.0 - 9.1 mg/l

LC50, tidewater silverside (Menidia beryllina), flow-through, 96 h: 4.28 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea Daphnia magna, static, 48 h, survival: 5.8 mg/l

EC50, eastern oyster (Crassostrea virginica), flow-through, 96 h, shell growth inhibition: 1.8 mg/l

EC50, water flea Daphnia magna, flow-through, 48 h, survival: 2.2 mg/l

Aquatic Plant Toxicity

EbC50, green alga Pseudokirchneriella subcapitata (formerly known as Selenastrum capricornutum), biomass growth inhibition, 72 h: 0.92 mg/l

ErC50, green alga Pseudokirchneriella subcapitata (formerly known as Selenastrum capricornutum), Growth rate inhibition, 72 h: 1.7 mg/l

Toxicity to Non-mammalian Terrestrial Species

oral LD50, mallard (Anas platyrhynchos): 2,708 mg/kg

dietary LC50, mallard (Anas platyrhynchos): 1,466 ppm

dietary LC50, Japanese quail (Coturnix coturnix japonica): > 820 mg/kg

dietary LC50, bobwhite (Colinus virginianus): 2,135 ppm

Toxicity to Soil Dwelling Organisms

LC50, Earthworm Eisenia foetida, adult, 15 d: 209 mg/kg

Data for Component: 1,2,4-Trimethylbenzene

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, fathead minnow (Pimephales promelas), flow-through, 96 h: 7.7 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, water flea Daphnia magna, 48 h: 3.6 mg/l

Data for Component: Xylene

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (Oncorhynchus mykiss), 96 h: 9.2 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea Daphnia magna, 48 h: 14.3 mg/l

Aquatic Plant Toxicity

EC50, green alga Pseudokirchneriella subcapitata (formerly known as Selenastrum capricornutum), biomass growth inhibition, 72 h: 3.2 - 4.9 mg/l

Data for Component: 1,3,5-Trimethylbenzene

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, Japanese medaka (Oryzias latipes), static, 48 h: 8.6 mg/l

Aquatic Invertebrate Acute Toxicity

LC50, water flea Daphnia magna, 24 h, immobilization: 50 mg/l

Aquatic Plant Toxicity

EC50, alga Scenedesmus sp., biomass growth inhibition, 48 h: 25 mg/l

EC50, alga Scenedesmus sp., Growth rate inhibition, 48 h: 53 mg/l

Data for Component: Cumene

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in most sensitive species).

Fish Acute & Prolonged Toxicity

LC50, rainbow trout (Oncorhynchus mykiss), static renewal, 96 h: 3.6 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, water flea Daphnia magna, 48 h, immobilization: 4.0 mg/l

Aquatic Plant Toxicity

EC50, green alga Pseudokirchneriella subcapitata (formerly known as Selenastrum capricornutum), biomass growth inhibition, 72 h: 2.6 mg/l

Toxicity to Non-mammalian Terrestrial Species

oral LD50, redwing blackbird (Agelaius phoeniceus): > 98 mg/kg

13. Disposal Considerations

If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. If the material as supplied becomes a waste, follow all applicable regional, national and local laws. This information presented below only applies to the material as supplied. The identification based on characteristic(s)

or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Issue Date: 11/17/2008

14. Transport Information

DOT Non-Bulk

NOT REGULATED

DOT Bulk

Proper Shipping Name: FLAMMABLE LIQUID, NOS

Technical Name: CONTAINS XYLENE RANGE AROMATIC SOLVENT Hazard Class: 3 ID Number: UN1993 Packing Group: PG III

IMDG

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Technical Name: CONTAINS XYLENE RANGE AROMATIC SOLVENT Hazard Class: 3 ID Number: UN1993 Packing Group: PG III

EMS Number: F-E,S-E **Marine pollutant.: No**

ICAO/IATA

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Technical Name: CONTAINS XYLENE RANGE AROMATIC SOLVENT Hazard Class: 3 ID Number: UN1993 Packing Group: PG III

Cargo Packing Instruction: 310
Passenger Packing Instruction: 309

Additional Information

Reportable quantity: 877 lb - XYLENE

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health HazardYesDelayed (Chronic) Health HazardYesFire HazardYesReactive HazardNoSudden Release of Pressure HazardNo

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

Component	CAS#	Amount	
1,2,4-Trimethylbenzene	95-63-6	18.9%	
Cumene	98-82-8	2.5%	
Xylene	1330-20-7	11.4%	

Issue Date: 11/17/2008

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS#	Amount	
Nitrapyrin	1929-82-4	22.2%	
Xylene	1330-20-7	11.4%	

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This product contains the following substances which are subject to CERCLA Section 103 reporting requirements and which are listed in 40 CFR 302.4.

Component	CAS#	Amount
Xylene	1330-20-7	11.4%
Cumene	98-82-8	2.5%

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

Component	CAS#	Amount	
Nitrapyrin	1929-82-4	22.2%	

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

Component	CAS#	Amount
Nitrapyrin	1929-82-4	22.2%

Toxic Substances Control Act (TSCA)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

16. Other Information

Hazard Rating System

NFPA Health Fire Reactivity 2 2 0

Revision

Identification Number: 50110 / 1016 / Issue Date 11/17/2008 / Version: 4.0

DAS Code: XRM-4786

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for
	activities such as exposure monitoring and medical surveillance if exceeded.

Issue Date: 11/17/2008

Dow AgroSciences LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.